

10-Port Gigabit Unmanaged Ethernet Switch

1*1000M SFP ports+9*10/100/1000M RJ45 ports



S200-10GP-S-AC



Non-blocking, low delay design



Plug and Play, PoE watch dog



Eco-friendly and energy-saving



| Product Overview

The S200 series of Ethernet switches adopts low power consumption design, which meets the requirements of green environmental protection and energy saving; all ports support auto-MDI/MDI-X and wire-speed forwarding, ensuring stable and reliable data transmission.

| Key Features

- Supports IEEE 802.3 af/at, PoE management, and PoE Watchdog;
- 4KV port lightning protection;
- ESD: contact 8KV, air 15KV;
- -10~50°C wide operating temperature range;
- Support MDI/MDIX

| Hardware Features

Model	S200-10GP-S-AC
Interface	1*1000M SFP ports+9*10/100/1000M RJ45 ports
Switching Capacity	20Gbps
Packets Forwarding Rate	14.88Mpps
MAC	2K
Port Buffer	12K
Transfer Delay	<10us
Power Supply	AC 100-240V 50/60Hz
	Empty Load Power: <6W
LED Indicators	P,link/active
PoE	1-8 ports support PoE
	IEEE 802.3 af/at standards
	PoE power:120W
	PIN Sequence: 1,2+/3,6-
Environment	Working Temperature: -10°C ~ 50°C
	Storage Temperature: -40°C ~ 70°C
	Working Humidity: 10%~95% non-condensing
	Storage Humidity: 10%~95% non-condensing

Model	S200-10GP-S-AC
DIP Specification	PoE seamless restart 250m long distance transmission 1-8 port port isolation Storm control
Size(W*D*H)	270*181*44mm
Weight	1.1KG
EMC	Power Surge Protection: 6KV/2KV Ethernet Port Surge Protection: 4KV/2KV Anti-static Interference: 8KV/15KV Free Drop: 0.5M
Certificate Compliance	CE/FCC/RoHS

| Product Dimensions

